

SUSTAPEEK Tubes - available from stock in 3000mm lengths (118")

Production capabilities and stock range of SUSTAPEEK tubes

Outer Diameter mm	Inner Diameter																		
	10	15	20	25	30	35	40	45	50	60	70	80	100	120	130	140	150	170	180
20	•	•																	
25	•	•	•																
30	•	•	•	•															
32		•	•	•															
36		•	•	•	•														
40			•	•	•	•													
45			•	•	•	•	•												
50			•	•	•	•	•	•											
56					•	•	•	•	•										
60					•	•	•	•	•	•									
70					•	•	•	•	•	•	•								
75						•	•	•	•	•	•								
80							•	•	•	•	•	•							
85							•	•	•	•	•	•							
90								•	•	•	•	•	•						
95								•	•	•	•	•	•	•					
100								•	•	•	•	•	•	•	•				
115									•	•	•	•	•	•	•	•			
125									•	•	•	•	•	•	•	•	•		
140										•	•	•	•	•	•	•	•	•	
150											•	•	•	•	•	•	•	•	•
160												•	•	•	•	•	•	•	•
170													•	•	•	•	•	•	•
200														•	•	•	•	•	•
210															•	•	•	•	•
260																•	•	•	•

In Stock from 1" O.D. up to 8 1/4" O.D.



SUSTAPEEK tubes work in a large variety of applications due to a wide range of outer and inner diameters.

■ = in stock / Further dimensions available upon request - please contact us at info@roechling-plastics.us

Product Features

- ⇒ Continuous use temperature of 480° F
- ⇒ Intrinsic flame retardancy UL 94 V0
- ⇒ Outstanding rigidity at high temperatures
- ⇒ Excellent chemical resistance
- ⇒ Good dimensional stability
- ⇒ Excellent hydrolysis resistance

Product Values

- ⇒ Better yields
- ⇒ Range of sizes
- ⇒ Availability from stock
- ⇒ Reduced material waste
- ⇒ 100% virgin resin
- ⇒ Lot/batch traceability

Röchling Engineering Plastics offers the most comprehensive product line in the USA and Canada including:

Polystone® M (UHMW-PE)
 Polystone® P (Polypropylene)
 Polystone® G (HDPE)

Sustamid® Nylon
 Sustarin® Acetal
 Susta HPM's



Röchling Engineering Plastics

903 Gastonia Technology Parkway

Dallas, NC 28034, USA

Phone: 704-922-7814

Fax: 704-922-7651

info@roechling-plastics.us

www.roechling-plastics.us